

ATTACHMENT ROTATOR

<http://tiny.cc/attachmentrotator>


FEATURES & BENEFITS

- **360° rotation**
- **Mounts between the attachment and the quick attach plate of the loader**

The attachment rotator is designed for a 360°, smooth, continuous motion in both directions. The attachment rotator is commonly used in many jobs for inverting and dumping loads.

Like the tilt adapters, the attachment rotator mounts between the attachment and the loader's attachment coupling plate. It is equipped with a hydraulic motor and a slewing ring that allows the 360° rotation. Maximum load capacity is 1.200 kg. The rotator attachment coupling plate is 255 mm further away from the machine's attachment coupling plate.

The attachment rotator is intended mainly for non-hydraulically operated attachments, but with the optional second auxiliary hydraulics outlet on the loader it is possible to use with hydraulically driven attachments also like a 4 in 1 bucket, pallet fork with hydraulic fork adjustment, grabbing tool, etc.. at the same time.

Model	Max tilt	Max Load*	Weight	Code
Attachment rotator	360 °	1200 kg (2645 lbs)	73 kg (161 lbs)	C890960

(*) verify the lifting capacity of the machine

Compatibility	1.1	2.3	4.2	5.2	5.3	6.3	7.2	8.4	8.5	11.6	11.9	EZ5	EZ7 EZ8
	Very compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Compatible	Not compatible

